VERIFICATION OF CONFORMITY

Applicant Name & Address	:	**Zhejiang Envertech Corporation Ltd.** **24th Floor, Jintong Mansion, Center of Headquarters, Huang tang Block Dong Cheng district Yongkang City, Zhejiang Province P.R.China**
Manufacture Name & Address	:	**Zhejiang Envertech Corporation Ltd.** **24th Floor, Jintong Mansion, Center of Headquarters, Huang tang Block Dong Cheng district Yongkang City, Zhejiang Province P.R.China**
Product(s)	:	**PV Microinverter**
Model(s)	:	**EVT248; EVT300; EVT500; EVT560**
Technical Specification	:	**IP67, Class I** ***Additional information on Annex I***
Brand name	:	**Envertech, SEEYES**
Relevant Standard(s)	:	**VDE-AR-N 4105: 2011-08** **DIN VDE V 0124-100: 2012-07**
Verification Number	:	**EFSH201712-V004**
Report Number(s)	:	**EFSH17090029-IE-07-L01**

NOTE 1: This verification is part of the full test report(s) and should be read in conjunction with it.

This is the result of tests carried out on those samples of the product referred to above which were submitted for testing, in accordance with the specification for the respective standards. The sample(s) of the tested product has been found to comply with the relevant standard listed on this verification at the time the tests were carried out.
The manufacturer shall file and keep the documentation according to the rules of the applicable standard(s) and shall consider changes of the standard(s) if relevant. Additional requirements may be applicable such as additional standard(s) or local laws.

Jack Gan
Supervisor
2017-12-04

Verification issued by: Eurofins Product Testing Service (Shanghai) Co., Ltd.
No. 395 West Jiangchang Road, Jing'an District, Shanghai, China Phone +86-21-61819181 Fax +86-21-61819180

ANNEX I

Verification of conformity Reference No.: EFSH201712-V004

Technical Specification	:	**EVT248:** **Input: Max. 54VDC, MPPT voltage range: 24-42VDC, Max. 9,5A, Isc PV:15A Max** **Output: 230VAC, 50/60Hz, 248W, 1,07A** **EVT300:** **Input: Max. 54VDC, MPPT voltage range: 24-42VDC, Max.9,5A, Isc PV:15A Max** **Output: 230VAC, 50/60Hz, 300W, 1,36A** **EVT500:** **Input: Max. 54VDC, dual MPPT voltage range: 24-42VDC, Max. 9,5A x 2, Isc PV:15Ax2 Max** **Output: 230VAC, 50/60Hz, 500W, 2,17A** **EVT560:** **Input: Max. 54VDC, dual MPPT voltage range: 24-42VDC, Max. 9,5A x 2, Isc PV:15Ax2 Max** **Output: 230VAC, 50/60Hz, 560W, 2,55A**

NOTE 1: This verification is part of the full test report(s) and should be read in conjunction with it.

This is the result of tests carried out on those samples of the product referred to above which were submitted for testing, in accordance with the specification for the respective standards. The sample(s) of the tested product has been found to comply with the relevant standard listed on this verification at the time the tests were carried out.
The manufacturer shall file and keep the documentation according to the rules of the applicable standard(s) and shall consider changes of the standard(s) if relevant. Additional requirements may be applicable such as additional standard(s) or local laws.

Jack Gan
Supervisor
2017-12-04

Verification issued by: Eurofins Product Testing Service (Shanghai) Co., Ltd.
No. 395 West Jiangchang Road, Jing'an District, Shanghai, China Phone +86-21-61819181 Fax +86-21-61819180